



DECLARATION OF PERFORMANCE
According to Construction Product Regulation (EU) No 305/2011 (CPR)
DoP No. 1488-CPD-0387/W-EN

1. Unique identification code of the product-type:
Polyester V300 & V410 / Polyester P165

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-11/0507, Section 3.3

Batch number : see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

GENERIC TYPE	<i>Injection anchor for use in masonry</i>
FOR USE IN	<i>Perforated masonry acc. ETA 11/0507, Annex 6 Covered sizes : M10</i>
CATEGORY	<i>c</i>
LOADING	<i>Static and quasi static</i>
MATERIAL	<i>zinc-plated steel : category w/d installation in wet substrate ; use in dry internal conditions only covered sizes : M10</i>
TEMPERATURE RANGE	<i>-40°C to +80°C : max long term temperature +50°C, max short term temperature +80°C</i>

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) : **Diager SAS, ZI, Rue Henri Moissan, 39802 POLIGNY cedex 2, FRANCE**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) : --

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V : **System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

INSTYTUT TECHNIKI BUDOWLANEJ PL 00-611 WARSZAWA

ETA-11/0507

on the basis of **ETAG 029**



The notified body 1488 performed under System 1

- (i) Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
 - (ii) Initial inspection of the manufacturing plant and of factory production control;
 - (iii) Continuous surveillance, assessment and evaluation of factory production control under system 1
- and issued the Certificate of Conformity 1488-CPD-0387/W.

9. Declared performance:

ESSENTIAL CHARACTERISTICS	DESIGN METHOD	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
CHARACTERISTIC RESISTANCE FOR TENSION	ETAG 029	ETA-11/0507, annex 7	ETAG 029
CHARACTERISTIC RESISTANCE FOR SHEAR	ETAG 029	ETA-11/0507, annex 7	
MINIMUM SPACING AND MINIMUM EDGE DISTANCE	ETAG 029	ETA-11/0507, annex 8	
DISPLACEMENT FOR SERVICEABILITY LIMIT STATE	ETAG 029	ETA-11/0507, annex 7	


Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :




 François DEFOUGERES
 President DIAGER
 Poligny, 28.06.2013

DIAGER
 Z.I. - Rue Henri Moissan - BP 90149
 39802 POLIGNY Cedex 2 - FRANCE
 Tél. + 33 (0)3 84 73 74 75 - Fax + 33 (0)3 84 73 74 76
 RCS LONS LE SAUNIER B 408 484 277 00920