POLYESTER P165, P300, P410



Page: 1

Compilation date: 21/01/2011 Revision date: 05/02/2014

Revision No: 4

## Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: POLYESTER P165, P300, P410

Product code: 46056/46058/45025&26

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

## 1.3. Details of the supplier of the safety data sheet

Company name: Diager France

Rue Henri Moissan BP 90149, 39802 Poligny Cedex France Tel: +33 3 (0) 384 737475 Fax: +33 3 (0) 384 737078 Email: <u>contact@diager.com</u>

1.4. Emergency telephone number

Emergency tel: 03 88 37 37 37

Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CHIP: Sens.: R43

Classification under CLP: Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: May cause sensitisation by skin contact.

2.2. Label elements

Label elements under CLP:

Hazard statements:	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
Signal words:	Warning
Hazard pictograms:	GHS07: Exclamation mark



Precautionary statements: P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

## POLYESTER P165, P300, P410

Page: 2

P272: Contaminated work clothing should not be allowed out of the workplace.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases:R43: May cause sensitisation by skin contact.Safety phrases:S2: Keep out of the reach of children.S24: Avoid contact with skin.S37: Wear suitable gloves.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

VINYL TOLUENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
246-562-2	25013-15-4	-: R10; Xn: R20; Xi: R36/37/38	Acute Tox. 4: H332; Asp. Tox. 1: H304; Eve Irrit. 2: H319; Flam. Lig. 3: H226	10-20%

#### 2-ETHYLHEXYL BENZOATE

226-641-8	5444-75-7	-: R53 Aquatic Chronic 4: H413		1-3%
HYDROPHILIC	C PYROGENIC S	SILICA - REACH registered number(s)	: 01-2119379499-16	
231-545-4	7631-86-9	Substance with a Community workplace exposure limit.	1-3%	
DIBENZOYL F	PEROXIDE			
202-327-6	94-36-0	E: R3; O: R7; Xi: R36; Sens.: R43	Skin Sens. 1: H317; Org. Perox. B:	1-3%

## 202-327-6 94-36-0 E: R3; O: R7; Xi: R36; Sens.: R43 Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319

## Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

## POLYESTER P165, P300, P410

Ingestion: If conscious, give half a litre of water to drink immediately. Do not induce vomiting.

Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Harmful if swallowed.

Inhalation: Hamful by inhalation.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical

powder. Carbon dioxide. Do not use halons.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Sealed, heated containers can pressurise leading to explosion. In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the area with water.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

#### Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Keep away from Heat and sources of ignition.

## POLYESTER P165, P300, P410

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Ensure lighting and electrical equipment are not a source of ignition. Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

## Section 8: Exposure controls/personal protection

8.1. Control parameters

## Hazardous ingredients:

### DIBENZOYL PEROXIDE

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

**Respirable dust** 

## 8.1. DNEL/PNEC Values

#### Hazardous ingredients:

#### DIBENZOYL PEROXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Oral	1.65 mg/kg bw/d	General Population	Systemic
DNEL	Dermal	3.3 mg/kg bw/d	General Population	Systemic
DNEL	Inhalation	2.9 mg/m3	General Population	Systemic

## 8.2. Exposure controls

Engineering measures:	Ensure there is exhaust ventilation of the area. Ensure all engineering measures
	mentioned in section 7 of SDS are in place.
Respiratory protection:	* Breathing protection is required in inadequately ventilated places. Gas/vapour filter,
	type A: organic vapours (EN141).
Hand protection:	* Protective gloves. Wear solvent proof gloves. Nitrile gloves. Rubber gloves.
	Recommended thickness of material >0.5 mm As the product is a preperation of several
	substances, the resistance of the glove material can not be calculated in advance and
	has therefore to be checked prior to the application.
Eye protection:	Safety glasses.
Skin protection:	Protective clothing.
Environmental:	Ensure all engineering measures mentioned in section 7 of SDS are in place.

## Section 9: Physical and chemical properties

## POLYESTER P165, P300, P410

		<b>Page:</b> 5
9.1. Information on basic phy	ysical and chemical properties	
State:	Paste	
Colour:	Variable	
Odour:	Sweet-smelling	
Oxidising:	Oxidising (by EC criteria)	
Solubility in water:	Insoluble	
Flammability limits %: lower:	* upper: *	
Flash point°C:	* Relative density: 1.56	
VOC g/I:	2.31	
9.2. Other information		
Other information:	* Solid suspension - classified as non-flammable according to results from Tes	st N.1
	test method for readily combustible solids.	
ection 10: Stability and rea	ctivity	
10.1. Reactivity		
Reactivity:	Stable under recommended transport or storage conditions.	
10.2. Chemical stability		
Chemical stability:	Stable under normal conditions. May polymerise on heating.	
10.3. Possibility of hazardous	s reactions	
Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage condition	าร.
10.4. Conditions to avoid		
Conditions to avoid:	Direct sunlight. Heat. Sources of ignition.	
10.5. Incompatible materials		

Materials to avoid: Reducing agents. Amines. Acids. Alkalis. Heavy metal compounds.

## 10.6. Hazardous decomposition products

Haz. decomp. products: If exposed to high temperatures it will emit hazardous fumes and smoke.

# Section 11: Toxicological information

11.1. Information on toxicological effects

## Hazardous ingredients:

### HYDROPHILIC PYROGENIC SILICA

IHL	RAT	1H LC50	2.2	mg/kg
ORL	RAT	LD50	5000	mg/kg

#### . . . . .

		SAFET	Y DATA	SHEET			
		POLYESTE	ER P165, F	P300, P410			
							Page:
SKN	RBT		LD50		2000	mg/kg	
ORL	RAT		LD50		5000		
VAPOURS	RAT		LD50		24.3	mg/kg	
Relevant effects for mixture	e:						
Effect		Route	Э		Basis	6	
Sensitisation		DRM		Hazardou	is: calculated		
Symptoms / routes of exposu	Ire						
<u> </u>		. h . imitetien			- 6 4		
	-	y be irritation an y be irritation an			of contact.		
Ingestion:	-		u reuness.				
Inhalation:							
	,						
Delayed / immediate effects:	Not applic	Not applicable.					
Other information:	Not applic	able.					
ction 12: Ecological inform	nation						
2.1. Toxicity							
Ecotoxicity values:	No data a	vailable					
2.2. Persistence and degrad							
rsistence and degradability:		voilabla					
2.3. Bioaccumulative potent							
Bioaccumulative potential:	No data a	vailable.					
2.4. Mobility in soil							
Mobility:	Insoluble i	in water.					
2.5. Results of PBT and vPv	B assessn	nent					
PBT identification:	This produ	uct is not identifi	ed as a PE	3T substand	ce.		
2.6. Other adverse effects							
Other adverse effects:	No data a	vailable.					
ction 13: Disposal conside	erations						
3.1. Waste treatment metho	de						
Disposal operations:							
	company.	Small quantities	s of the pro	oduct can b	e mixed and allowed	d to cure, then c	an be

disposed as solid waste.

## POLYESTER P165, P300, P410

Waste code number: 08 04 12

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

#### Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
	Active Oxygen Content of Catalyst Component 0.99%
Phrases used in s.2 and 3:	H226: Flammable liquid and vapour.
	H241: Heating may cause a fire or explosion.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
	H413: May cause long lasting harmful effects to aquatic life.
	R3: Extreme risk of explosion by shock, friction, fire or other sources of ignition.
	R7: May cause fire.
	R10: Flammable.
	R20: Harmful by inhalation.
	R36/37/38: Irritating to eyes, respiratory system and skin.
	R36: Irritating to eyes.
	R43: May cause sensitisation by skin contact.
	R53: May cause long-term adverse effects in the aquatic environment.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.

## POLYESTER P165, P300, P410

**Page:** 8

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing please mix any waste product to its cured state.