

CONCRETE DRILL BIT

INTENSIVE USE

MEGA

Ref.
226




Features

- Carbide tip with semi-positive shaped.
- "U" shaped flute.
- Polished finish.
- Straight shank.

Benefits

- Polish finish with striking appeal permits dust removal.



Ø	Lu	Lt	Ref.	Gencod	Qt.
Short series					
3	20	60	226D03	3336600028296	1
4	35	75	226D04	3336600028302	1
5	45	85	226D05	3336600028319	1
5,5	45	85	226D05,5	3336600028470	1
6	60	100	226D06	3336600028326	1
6,5	60	100	226D06,5	3336600028487	1
7	60	100	226D07	3336600028333	1
8	80	120	226D08	3336600028340	1
9	80	120	226D09	3336600028357	1
10	80	120	226D10	3336600028364	1
11	110	150	226D11	3336600028371	1
12	110	150	226D12	3336600028388	1
13	110	150	226D13	3336600028395	1
14	110	150	226D14	3336600028401	1
15	110	150	226D15	3336600028418	1
16	110	150	226D16	3336600028425	1
18	120	160	226D18	3336600028432	1
20	120	160	226D20	3336600028449	1
22	120	160	226D22	3336600056749	1
L150					
5	110	150	226D05L0150	3336600049062	1
5,5	110	150	226D05,5L0150	3336600062719	1
6	110	150	226D06L0150	3336600049079	1
8	110	150	226D08L0150	3336600049093	1
10	110	150	226D10L0150	3336600049116	1
L200					
6	160	200	226D06L0200	3336600062740	1
8	160	200	226D08L0200	3336600049123	1
10	160	200	226D10L0200	3336600049130	1
12	160	200	226D12L0200	3336600049147	1
14	160	200	226D14L0200	3336600049154	1
16	160	200	226D16L0200	3336600049161	1
L400					
6	360	400	226D06L0400	3336600049178	1
8	360	400	226D08L0400	3336600049192	1
10	360	400	226D10L0400	3336600049215	1
12	360	400	226D12L0400	3336600049239	1
14	360	400	226D14L0400	3336600049253	1
16	360	400	226D16L0400	3336600049277	1
18	360	400	226D18L0400	3336600049284	1
20	360	400	226D20L0400	3336600049291	1



SETS
PAGE
57

211C 256C



Ø Max 12.7

FAST

Pro

264




Features

- Carbide tip with semi-positive shaped.
- Double-rolled thread flute with land.
- Polished finish.
- Straight shank.

Benefits

- The head design permits faster drilling.



Ø	Lu	Lt	Ref.	Gencod	Qt.
Short series					
3	20	60	264D03	3336600056060	1
3,5	35	75	264D03,5	3336600056077	1
4	45	85	264D04	3336600056084	1
4,5	45	85	264D04,5	3336600056091	1
5	55	95	264D05	3336600056107	1
5,5	60	100	264D05,5	3336600056114	1
6	60	100	264D06	3336600056121	1
6,5	80	100	264D06,5	3336600056138	1
7	80	100	264D07	3336600056145	1
8	80	120	264D08	3336600056152	1
9	80	120	264D09	3336600056169	1
10	80	120	264D10	3336600056176	1
11	110	150	264D11	3336600056183	1
12	110	150	264D12	3336600056190	1
13	110	150	264D13	3336600056206	1
14	110	150	264D14	3336600056213	1
16	110	150	264D16	3336600056237	1
18	120	160	264D18	3336600056244	1
19	120	160	264D19	3336600099401	1
20	120	160	264D20	3336600056251	1
L150					
5	110	150	264D05L0150	3336600056268	1
6	110	150	264D06L0150	3336600056275	1
7	110	150	264D07L0150	3336600056282	1
8	110	150	264D08L0150	3336600056299	1
10	110	150	264D10L0150	3336600056312	1
L200					
6	160	200	264D06L0200	3336600056329	1
8	160	200	264D08L0200	3336600056343	1
10	160	200	264D10L0200	3336600056350	1
12	160	200	264D12L0200	3336600056367	1
14	160	200	264D14L0200	3336600056374	1



SETS
PAGE
57

208D



201C

299B



Ø Max 12.7