

Surface protection sockets

Features

- Attachment DIN 3126 E 6,3.
- For hex head screw.
- Mechanical screw holding system (ball/spring).

Benefits

- Specially adapted for screws used for fastening fronts or sandwich panels and self-drilling screws.
- The system that holds the screw head in the socket is specially designed for working with painted or plastic finishes.



Designation	Qt.	Lt	Ref.	Gencod	Qt.
S07	1		U601S07	3336600181632	1
S08	1		U601S08	3336600181649	1
S10	1		U601S10	3336600181656	1
S1/4 (6.35 mm)	1		U601S1/4	3336600181663	1
S5/16 (8 mm)	1		U601S5/16	3336600181670	1
S3/8 (9.5mm)	1		U601S3/8	3336600181687	1



U601

Ref.

U601



DIN 3126 E6.3

Pro magnetic sockets

Features

- Attachment DIN 3126 E 6,3.
- For hex head screw.
- Permanent magnet.

Applications

- Powerful magnet for holding screws.

Designation	Qt.	Lt	Ref.	Gencod	Qt.
L 50					
S1/4 (6,35 mm)	1	50	U600S0.025	3336600172302	1
S05.5	1	50	U600S05.5	3336600187276	1
S06	1	50	U600S06	3336600173118	1
S07	1	50	U600S07	3336600172319	1
S08	1	50	U600S08	3336600172326	1
S09	1	50	U600S09	3336600190276	1
S10	1	50	U600S10	3336600172340	1
S12	1	50	U600S12	3336600172357	1
S13	1	50	U600S13	3336600172364	1
L 65					
S05	1	65	U603S05	3336600187368	1
S05.5	1	65	U603S05.5	3336600187375	1
S06	1	65	U603S06	3336600187382	1
S07	1	65	U603S07	3336600187399	1
S08	1	65	U603S08	3336600187283	1
S10	1	65	U603S10	3336600187290	1
S12	1	65	U603S12	3336600190283	1
S13	1	65	U603S13	3336600187313	1



U602

U600
U603



DIN 3126 E6.3

Adapter

Features

- Standard 1/4 square socket holder.
- Quick lock attachment for optimum holding in the chuck.



Designation	Qt.	Lt	Ref.	Gencod	Qt.
Sockets	1	50	U636	3336600178236	1

U636



DIN 3126 E6.3

Stopvis



Designation	Qt.	Lt	Ref.	Gencod	Qt.
2 Stopvis PH2	2	25	627PH2	3336600146778	1
2 Stopvis PZ2	2	25	627PZ2	3336600146785	1

627



DIN 3126 C6.3