

# Surface protection sockets

### Features

- Attachment DIN 3126 E 6,3.
- For hex head screw.
- Mechanical screw holding system (ball/spring).

### Benefits

- Specially adapted for screws used for fastening fronts or sandwich panels and self-drilling screws.
- The system that holds the screw head in the socket is specially designed for working with painted or plastic finishes.



| Designation           | Qt. | Lt | Ref.      | Gencod        | Qt. |
|-----------------------|-----|----|-----------|---------------|-----|
| <b>S07</b>            | 1   |    | U601S07   | 3336600181632 | 1   |
| <b>S08</b>            | 1   |    | U601S08   | 3336600181649 | 1   |
| <b>S10</b>            | 1   |    | U601S10   | 3336600181656 | 1   |
| <b>S1/4 (6.35 mm)</b> | 1   |    | U601S1/4  | 3336600181663 | 1   |
| <b>S5/16 (8 mm)</b>   | 1   |    | U601S5/16 | 3336600181670 | 1   |
| <b>S3/8 (9.5mm)</b>   | 1   |    | U601S3/8  | 3336600181687 | 1   |



U601

Ref.

U601



DIN 3126 E6.3

# Pro magnetic sockets

### Features

- Attachment DIN 3126 E 6,3.
- For hex head screw.
- Permanent magnet.

### Applications

- Powerful magnet for holding screws.

| Designation           | Qt. | Lt | Ref.       | Gencod        | Qt. |
|-----------------------|-----|----|------------|---------------|-----|
| <b>L 50</b>           |     |    |            |               |     |
| <b>S1/4 (6,35 mm)</b> | 1   | 50 | U600S0.025 | 3336600172302 | 1   |
| <b>S05.5</b>          | 1   | 50 | U600S05.5  | 3336600187276 | 1   |
| <b>S06</b>            | 1   | 50 | U600S06    | 3336600173118 | 1   |
| <b>S07</b>            | 1   | 50 | U600S07    | 3336600172319 | 1   |
| <b>S08</b>            | 1   | 50 | U600S08    | 3336600172326 | 1   |
| <b>S09</b>            | 1   | 50 | U600S09    | 3336600190276 | 1   |
| <b>S10</b>            | 1   | 50 | U600S10    | 3336600172340 | 1   |
| <b>S12</b>            | 1   | 50 | U600S12    | 3336600172357 | 1   |
| <b>S13</b>            | 1   | 50 | U600S13    | 3336600172364 | 1   |
| <b>L 65</b>           |     |    |            |               |     |
| <b>S05</b>            | 1   | 65 | U603S05    | 3336600187368 | 1   |
| <b>S05.5</b>          | 1   | 65 | U603S05.5  | 3336600187375 | 1   |
| <b>S06</b>            | 1   | 65 | U603S06    | 3336600187382 | 1   |
| <b>S07</b>            | 1   | 65 | U603S07    | 3336600187399 | 1   |
| <b>S08</b>            | 1   | 65 | U603S08    | 3336600187283 | 1   |
| <b>S10</b>            | 1   | 65 | U603S10    | 3336600187290 | 1   |
| <b>S12</b>            | 1   | 65 | U603S12    | 3336600190283 | 1   |
| <b>S13</b>            | 1   | 65 | U603S13    | 3336600187313 | 1   |



U602



U600  
U603



DIN 3126 E6.3

# Adapter

### Features

- Standard 1/4 square socket holder.
- Quick lock attachment for optimum holding in the chuck.



| Designation    | Qt. | Lt | Ref. | Gencod        | Qt. |
|----------------|-----|----|------|---------------|-----|
| <b>Sockets</b> | 1   | 50 | U636 | 3336600178236 | 1   |

U636



DIN 3126 E6.3

# Stopvis



| Designation          | Qt. | Lt | Ref.   | Gencod        | Qt. |
|----------------------|-----|----|--------|---------------|-----|
| <b>2 Stopvis PH2</b> | 2   | 25 | 627PH2 | 3336600146778 | 1   |
| <b>2 Stopvis PZ2</b> | 2   | 25 | 627PZ2 | 3336600146785 | 1   |

627



DIN 3126 C6.3